




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B60R 11/02, H04R 7/06		A1	(11) International Publication Number: WO 99/11490
			(43) International Publication Date: 11 March 1999 (11.03.99)
(21) International Application Number: PCT/GB98/02533 (22) International Filing Date: 24 August 1998 (24.08.98) (30) Priority Data: 9718627.4 3 September 1997 (03.09.97) GB 9807318.2 7 April 1998 (07.04.98) GB (71) Applicant (for all designated States except US): NEW TRANS- DUCERS LIMITED [GB/GB]; Stonehill, Huntingdon, Cam- bridgeshire PE18 6ED (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): AZIMA, Henry [CA/GB]; 3 Southacre Close, Chaucer Road, Cambridge CB2 2TT (GB). COLLOMS, Martin [GB/GB]; 22 Burgess Hill, London NW2 2DA (GB). ELLIS, Christien [GB/GB]; Briar Cottage, 3 Barley Road, Great Chishill, Hertfordshire SG8 8SB (GB). (74) Agent: MAGUIRE BOSS; 5 Crown Street, St. Ives, Cam- bridgeshire PE17 4EB (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: TRIM PANEL COMPRISING AN INTEGRAL ACOUSTIC SYSTEM



(57) Abstract

A trim panel, e.g. a roof lining for a vehicle passenger compartment, characterised in that the trim panel comprises an integral acoustic radiator and a vibration exciter mounted on the radiator to launch bending waves into the radiator to cause it to resonate to produce an acoustic output, and means integral with the radiator to define the radiator periphery.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

5

TRIM PANEL COMPRISING AN INTEGRAL ACOUSTIC SYSTEM

DESCRIPTION

10

15

TECHNICAL FIELD

The invention relates to trim panels, e.g. for the passenger cabin of a vehicle such as an automobile and more particularly to trim panels incorporating loudspeakers.

20

BACKGROUND ART

A number of approaches have been tried for achieving good quality sound reproduction in vehicles such as automobiles. Conventional pistonic loudspeakers of good quality, efficiency and satisfactory loudness use large
25 magnets driving cone diaphragms resulting in an assembly including the loudspeaker chassis or basket of appreciable depth typically 6 to 10 cm.

Space is limited in a vehicle interior with little

scope for sealed or tuned box volumes typically used for cone-type pistonic speakers. Often speakers have to be installed in non optimal positions well away from the head locations of the occupants, for example, on the rear parcel shelf, on the lower door panels out of the way of the window winder mechanism, or at the extremities of the dashboard, to supplement the sound from the poorly located door speakers. Six speaker arrangements are typical in an attempt to address the problems caused by poor location driven by the need to find significant panel depth to locate conventional speaker drivers.

Rear parcel shelf speakers are located behind the passengers, far from the front seats and are impaired by proximity to the cavity formed by the rear window glass and the parcel shelf. Potentially each such speaker is also located too near the nearest passenger resulting in a local excess of loudness.

Door-mounted speakers are placed in the noisiest part of the vehicle and suffer from vibration, door panel resonance, road noise transmission and engine noise. They are almost inaudible for rear seat passengers and are placed well off axis for front seat occupants. In addition their acoustic output may be severely obstructed by an occupant's leg(s).

A further pair of loudspeakers which may be located on the dashboard often suffer from poor mounting technique impairing the frequency response and endure local reflections from the windscreen glass. They are

inadequately placed to give satisfactory spread of the two stereo channels. Each is usually too near to the nearest occupant.

In our International patent application WO97/09844, these problems are addressed with the object of giving greater aural comfort, reduced installation cost, greater signal to noise ratio, greater efficiency, more uniform stereo and multi channel sound for all the vehicle occupants, reduced weight, simplified vehicle wiring and potentially higher quality sound.

Distributed mode bending wave resonant panel loudspeakers as described in our International application WO97/09842 use a diaphragm which is usually flat and is relatively slim, driven by a low excursion low profile electromechanical transducer, typically electrodynamic although other types are suitable including piezo, if the acoustic characteristics of the radiating panel are satisfactorily matched to the type of transducer and to the available amplification.

20 DISCLOSURE OF INVENTION

From one aspect the present invention is a vehicle having a passenger compartment, a trim panel, e.g. a roof lining, forming a lining in the passenger compartment and a loudspeaker in the passenger compartment, characterised in that the loudspeaker is in the trim panel and comprises an integral resonant acoustic radiator and a vibration exciter mounted on the radiator to launch bending waves into the radiator to cause it to resonant to produce an

acoustic output, and means integral with the radiator and defining the radiator periphery. The integral periphery defining means may be moulded integrally with the trim panel or may be permanently fixed to the trim panel to make it integral therewith. Equally, the acoustic radiator may be moulded integrally with the trim panel or may be permanently fixed thereto to make it integral therewith. Possibly the periphery defining means could be moulded integrally with the trim panel and the acoustic radiator could be permanently fixed to the trim panel, e.g. by adhesive means, to make it integral therewith.

The radiator may be of the same material as the trim panel or may comprise a stiff lightweight panel. The integral periphery defining means may define a clamped edge termination for the radiator. The clamped edge termination may be formed by an integrally moulded stiffening rib surrounding the radiator.

The radiator may be stiffened by one or more ribs extending over its surface.

20 The vibration exciter may be inertial. The vibration exciter may be electrodynamic.

From another aspect the invention is a trim panel, e.g. a roof lining for a vehicle passenger compartment, characterised in that the trim panel comprises an integral acoustic radiator and a vibration exciter mounted on the radiator to launch bending waves into the radiator to cause it to resonate to produce an acoustic output, and means integral with the radiator to define

the radiator periphery.

The radiator may comprise a stiff lightweight panel.

The integral peripheral means may define a clamped edge termination for the radiator. The clamped edge termination may be formed by an integrally moulded stiffening rib surround the radiator.

The radiator may be stiffened by at least one rib extending over its surface.

The vibration exciter may be inertial. The vibration exciter may be electrodynamic.

The trim panel may comprise a plurality of resonant radiators. Where the trim panel is a vehicle roof lining for a passenger compartment, a resonant radiator may be positioned adjacent to each passenger position in the compartment.

It is fundamental to the present invention that the designated sound radiating area is of the distributed mode type in the required frequency range. In contrast to other kinds of radiator, e.g. near pistonic and local area excited types which have essentially point source coherent radiation characteristics, the distributed mode type is excited over a significant area and has a diffuse non-directional output even at extreme off axis angles, without significant variation with frequency. This provides a good radiation pattern for the confined spaces within a vehicle passenger cabin.

The panel may be adapted to operate at least partly below coincidence frequency, and may be adapted to operate

mainly or wholly below coincidence frequency.

The entire periphery of the acoustic member may be clamped or alternatively one or more edges of the member, e.g. a rectangular panel, may be clamped. Full clamping enables the design of the loudspeaker assembly to be predictable in mechanical terms, and also facilitates the creation of a loudspeaker assembly which is relatively robust in construction, compared to a resonant panel loudspeaker in which the panel edges are free or are resiliently suspended.

The clamping of the peripheral portion(s) or edge(s) of the acoustic member may be achieved in any desired manner e.g. by rigidly fixing the edge(s) to a frame or the like by means of an adhesive or by mechanical means e.g. involving clamping the edge(s) between frame members.

The edge clamping may also be achieved by moulding techniques such as injection moulding of plastics materials by forming the edges of the member with integral thickened surround portions of sufficient rigidity to terminate edge movement of the acoustic member. Co-moulding of the acoustic member and the thickened edge may be appropriate. Such moulding techniques may be particularly suitable where the acoustic member is formed as a monolith and may be readily achievable in economic manner.

It will thus be appreciated that the term 'clamped edge' is intended to encompass all forms of edge restraint.

Clamping may also be used to define one acoustic member within another larger acoustic member. Thus a large acoustic panel intended for mid/low frequency operation may be moulded to include a smaller high
5 frequency acoustic panel defined by a clamped perimeter formed by stiffening ribs.

The clamping action can be designed to have a desired mechanical termination impedance to control the reverberation time within the acoustic member as an aid to
10 control of the frequency response of the member especially at lower frequency registers by introducing suitable damping.

The acoustic member may be rectangular and the aspect ratio may be as described in International patent
15 application No. WO97/09842; the acoustic member may be of constant thickness; the bending stiffness of the acoustic member may be isotropic, the objective of these measures being to maximise modal density in the member for the reasons explained in International patent application No.
20 WO97/09842.

The clamping of the panel edges enables the use of relatively low stiffness panels which will assist in reducing the fundamental bending mode of the panel below levels achievable for stiffer panels. This may facilitate
25 the enhancement of low frequency performance.

Thus, for example, where the range of stiffness for a practical example of a free edge panel of the kind described in International patent application No.

WO97/09842 may be of the order of 0.1 to 50Nm, the stiffness of a clamped edge panel of the same general kind may be greater than 0.001 Nm. Also where the range of surface density of the said practical example of free edge panel may be 100 to 1000 g/m², the density of the clamped edge panel may be greater than 25 g/m². It will, however, be appreciated that significantly stiffer and/or denser materials may be employed for the acoustic panel where low frequency performance is not a requirement.

10 Consequences arising from edge clamping an acoustic member include:-

1. the frequency of the first bending mode (f_0) rises by about ten-fold, and
2. three lower modes, which are absent for a free boundary panel, become useful. These lower modes can be useful in recovering losses due to the raised f_0 . Indeed preliminary tests show that for an acoustic panel of given mechanical properties, edge clamping provides a significant gain in the low frequency acoustic energy output.

20 Also the use of panels or panel materials of relatively low rigidity may enable the coincidence frequency to be moved upwards, perhaps above the audio band, which may improve the uniformity of sound directivity from the panel. At the same time, with less rigid panels, the modal density in the lower registers may be augmented, with a consequent improvement in sound

quality.

The radiating member may be excited in any of the ways suggested in International patent application No. WO97/09842, e.g. by way of an inertial electro-mechanical 5 exciter device. The or each exciter may be arranged to excite the radiating member at any suitable geometric position(s) on the acoustic member e.g. as disclosed in International patent application No. WO97/09842 or otherwise, again with the objective of optimising modal 10 density.

More than one such panel may be incorporated in the trim panel, e.g. a roof lining of a vehicle. With two panels these may be placed approximately half way between front and rear occupants serving them similarly well. A 15 number of different arrangements are also possible, as follows:-

1. Installed wide frequency range distributed mode panel operating alone as a two-speaker system.
2. Smaller distributed mode speaker panels for mid and 20 upper frequencies located in the roof section operating in conjunction with conventional cone speakers for low frequencies, e.g. door or rear parcel shelf, or box type sub woofers suitably installed.
- 25 3. Smaller distributed mode speaker panels according to paragraph 2 above, distributed in greater numbers for still better even sound distribution and/or to account for other installations in the vehicle roof

e.g. a sunroof.

4. The installation may be visible with simple framing, fixed by screws or by self-locking clips commonly used in auto installations. Alternatively the roof lining may be made acoustically transparent in the region of the distributed mode loudspeaker, e.g. by choice of materials and/or micro perforation, facilitating the fixing of the panel speaker to the back of the lining for an invisible installation.
5. At lowest frequencies where the radiation efficiency of the panel speaker is reduced, the roof lining may then be used to maintain the acoustic output. This lining may be designed and fabricated to achieve an installed mechanical impedance and broad band low frequency resonances to act as a large area bending wave radiator adapted to the low frequency range. The distributed mode speaker panel may be coupled by a suitable terminating compliance to the perimeter of the speaker aperture so as to extend the influence of the driver transducer located on the distributed mode speaker panel to the acoustically operative region of the roof lining. At low frequencies, the distributed mode panel is relatively stiff and the primary coupled mechanical impedance at low frequencies is then the roof lining. This may be a light semi-flexible composite of bonded fibre or pulp of good damping, moderate mass and faced with a thin acoustic foam of 2 to 4mm thickness and may be covered with a

decorative fabric or soft perforated polymer film.

6. Fabrication techniques also allow for distributed mode speakers to be formed as a largely integral component of the roof lining. In design the speaker regions are designated and delineated by suitable perimeter compliance, e.g. slotting, grooving, ridging etc. of the structural backing. Distributed mode panel operation is obtained by additional treatment of the speaker regions, such as laminating skins, additional reinforcement, resin impregnation.

The electro-mechanical vibration exciter may be mounted directly to the designated region at optimal distributed mode drive points, or via a coupling plate providing/or defined mechanical impedances to optimise the frequency characteristics and the blend between the mid treble speaker panel and the larger coupled radiator.

By this means loudspeakers may be integrated directly in the fabrication of the roof lining, to provide an increased value sub-assembly for car component makers.

7. A region of the roof lining may be designed for distributed bending wave operation by suitable skin shape, ridging, area geometry design and may be driven directly by a low frequency electromechanical exciter while the mid and high frequencies may be reproduced by additional distributed mode speakers, separately made, excited and mounted in acoustically

porous apertures in the roof lining compliantly mounted relative to their frame or perimeter.

Additionally these mid to high frequency distributed mode reproducers may also be integrated with the lining by 5 suitable delineation, compliant periphery, and/or local reinforcement techniques.

BRIEF DESCRIPTION OF DRAWINGS

The invention is diagrammatically illustrated, by way of example, in the accompanying drawings, in which:-

10 Figure 1 is a plan view of the roof or headlining for an automobile having integral resonant panel loudspeakers;

Figure 2 is a partial cross-sectional view on the line Y-Y of Figure 1;

Figure 2a is an enlarged view of a detail shown 15 circled in Figure 2;

Figure 3 is a plan view of second embodiment roof or headlining for an automobile;

Figure 4 is a partial cross-sectional side view of the embodiment of Figure 2;

20 Figure 5 is a plan view of a third embodiment of automobile roof or headlining;

Figure 6 is a partial cross-sectional side view of the embodiment of Figure 5;

Figure 7 is a partial cross-sectional side view, 25 generally corresponding to that of Figure 6, of another embodiment of automobile roof or headlining;

Figure 8 is a partial cross-sectional side view, generally corresponding to that of Figure 7, of another

embodiment of automobile roof or headlining, and

Figure 9 is a partial cross-sectional side view, generally corresponding to that of Figure 6, of yet another embodiment of automobile roof or headlining.

5 BEST MODES FOR CARRYING OUT THE INVENTION

In Figures 1 and 2 of the drawings, there is shown a trim panel in the form of a roof or headlining (1) for an automobile (not shown) in which the relative head positions of four passengers or occupants (2) are shown.
10 A roof light (3) is provided in the roof lining (1) near to its front end (4). Four similar distributed mode acoustic radiator loudspeakers (5), of the kind generally described in our International patent application PCT/GB96/02145 (WO97/09842) are located in the roof lining
15 so that respective ones of the radiators (5) are positioned adjacent to and slightly in front of the head of each occupant (2).

As shown in Figures 2 and 2a, the radiators (5) are formed, e.g. moulded, integrally with the roof lining. A
20 transducer or exciter (6), which may be an electrodynamic inertial device, is mounted on the radiator (5) to launch bending waves into the radiator to cause it to resonate to produce an acoustic output in the manner described in our International patent application WO97/09842.

25 The edge (7) of each radiator panel is defined by a thinned portion of the roof lining to provide a clamped edge termination to each panel. The thinned portion (7) comprises a corrugation (12) extending round the edge of

the panel.

As indicated, the roof lining comprises opposed skins (8) enclosing a resilient core (9), e.g. of a soft foam material. Similarly the radiator comprises opposed skins 5 (10) but of high modulus, enclosing a core (11) which may be of rigid foam or honeycomb, to provide a stiff lightweight resonant radiator panel.

As shown in Figure 2a, the upper skin (8) of the roof lining is overlapped with the lower skin (10) of the 10 radiator at the corrugation (12) to provide a good bond between the radiator and the headlining whereby they are integrated.

Figures 3 and 4 show a trim panel in the form of an automobile roof or headlining (1) which is generally 15 similar to that of Figures 1 and 2. In this case a headlining laminate comprising opposed skins (8) enclosing a core (9) which is compressed in an area (5) forming a resonant panel loudspeaker e.g. of the kind described in International patent application WO97/09842 to a reduced 20 thickness indicated by the darker shading of the core material (11) and which is formed during the compression process forming the headlining with raised ribs (13) extending from the rear face and which form a grid pattern (14) as indicated in Figure 3 to stiffen the loudspeaker 25 panel as desired. The edge (7) of the loudspeaker panel is defined by a groove (19) formed by a greater degree of compression of the headlining laminate and which forms a clamped edge surround. A rear view mirror (15) is shown

at the front (4) of the headlining (1).

The headlining of Figures 5 and 6 is generally similar to that described in Figures 3 and 4 with the exception that the loudspeaker panels (5) are compressed 5 from the general thickness of the headlining material and are each formed with a groove (19) surrounding and defining the edge (7) of the panel (5) and forming a clamped edge surround, but without forming a grid of raised stiffening ribs.

10 The headlining (1) of Figure 7 is provided with upstanding rib formations (16) which surround and define resonant loudspeaker panels (5) within the general area of the headlining and which stiffen the edges (7) of the respective loudspeaker panel (5) to form a clamped 15 surround. The upstanding rib formations (16) are formed in any convenient manner, e.g. by moulding, and are applied to one side of the headlining laminate (8,9) e.g. by means of an adhesive to integrate the rib formation with the headlining.

20 The headlining (1) of Figure 8 is very similar to that of Figure 7 in that it is formed with a clamped edge (7) formed by an upstanding stiffening rib (16) surrounding the radiator panel (5), and in this case that area of the headlining core (9) forming the radiator core 25 (11) is compressed to be thinner than the general thickness of the headlining (1) as indicated by heavier shading. Also in this embodiment the raised rib (16) is moulded integrally with the headlining. It will be noted

that the area of the radiator (5) bounded by the rib (16) is reinforced by a stiffening sheet (17) of any suitable material applied to a skin (8) of the laminate and bonded thereto.

5 The headlining of Figure 9 comprises a thinned region and defining an acoustically active area of the headlining and forming a resonant loudspeaker panel (5), bounded by a step or lip (18) visible on the rear face of the headlining and which forms a clamped edge surround (7),
10 e.g. of the kind defined in WO97/09842. The headlining (1) may be of the laminated kind described above or may be a resin impregnated fibrous body.

INDUSTRIAL APPLICABILITY

It will be appreciated that although the invention
15 has been particularly described with reference to a head or roof lining of an automobile, the invention applies also to other vehicles and to other objects requiring one or more trim panels as a lining. Also the invention applies to other trim panels within vehicles, e.g. to door
20 panels, dashboards and rear parcels shelves.

CLAIMS

1. A vehicle having a passenger compartment, a trim panel lining the passenger compartment and a loudspeaker
5 in the passenger compartment, characterised in that the loudspeaker is in the trim panel and comprises an integral resonant acoustic radiator and a vibration exciter mounted on the radiator to launch bending waves into the radiator to cause it to resonant to produce an acoustic output, and
10 means integral with the radiator and defining the radiator periphery.
2. A vehicle according to claim 1, characterised in that the radiator comprises a stiff lightweight panel.
3. A vehicle according to claim 1 or claim 2,
15 characterised in that the integral means defines a clamped edge termination for the radiator.
4. A vehicle according to claim 3, characterised in that the clamped edge termination is co-extensive with the integral radiator periphery defining means.
- 20 5. A vehicle according to claim 3 or claim 4, characterised in that the clamped edge termination is formed by a stiffening rib surrounding the radiator.
6. A vehicle according to claim 3 or claim 4, characterised in that the clamped edge termination is
25 defined by a step in thickness between the radiator and the thin panel lining.
7. A vehicle according to any preceding claim, characterised in that the radiator is stiffened by at

least one rib extending over its surface.

8. A vehicle according to any one of claims 1 to 6, characterised by a stiffening sheet applied to one surface of the radiator.

5 9. A vehicle according to any preceding claim, characterised in that the vibration exciter is inertial.

10. A vehicle according to any preceding claim, characterised in that the vibration exciter is electrodynamic.

10 11. A vehicle according to any preceding claim, characterised in that the trim panel is a roof lining.

12. A trim panel, e.g. a roof lining for a vehicle passenger compartment, characterised in that the trim panel comprises an integral acoustic radiator and a
15 vibration exciter mounted on the radiator to launch bending waves into the radiator to cause it to resonate to produce an acoustic output, and means integral with the radiator to define the radiator periphery.

13. A trim panel according to claim 12, characterised in
20 that the radiator comprises a stiff lightweight panel.

14. A trim panel according to claim 12 or claim 13, characterised in that the integral means defines a clamped edge termination for the radiator.

15. A vehicle according to any one of claims 12 to 14,
25 characterised in that the clamped edge termination is co-extensive with the integral radiator periphery defining means.

16. A trim panel according to claim 14 or claim 15,

characterised in that the clamped edge termination is formed by a stiffening rib surrounding the radiator.

17. A vehicle according to claim 14 or claim 15, characterised in that the clamped edge termination is
5 defined by a step in thickness between the radiator and the thin panel lining.

18. A trim panel according to any one of claims 12 to 17, characterised in that the radiator is stiffened by at least one rib extending over its surface.

10 19. A vehicle according to any one of claims 12 to 18, characterised by a stiffening sheet applied to one surface of the radiator.

20. A trim panel according to any one of claims 12 to 19, characterised in that the vibration exciter is inertial.

15 21. A trim panel according to any one of claims 12 to 20, characterised in that the vibration exciter is electrodynamic.

22. A trim panel as claimed in any one of claims 12 to 21, characterised by a plurality of resonant radiators.

20 23. A trim panel according to any one of claims 12 to 22, characterised in that the trim panel is a vehicle roof lining for a passenger compartment and in that a resonant radiator is positioned adjacent to each passenger position.




FIG. 1

2 / 5




FIG. 2




FIG. 2a

3 / 5




FIG. 3




FIG. 4

4 / 5




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/02533

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B60R11/02 H04R7/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B60R H04R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 007, no. 020 (M-188), 26 January 1983 & JP 57 175444 A (NISSAN JIDOSHA KK), 28 October 1982 see abstract	1, 2, 12, 13, 22
A	---	3-11, 14-21, 23
X	PATENT ABSTRACTS OF JAPAN vol. 007, no. 020 (M-188), 26 January 1983 & JP 57 175445 A (NISSAN JIDOSHA KK), 28 October 1982 see abstract	1, 2, 12, 13
A	---	3-11, 14-23
	--- -/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

28 December 1998

Date of mailing of the international search report

05/01/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

D'sylva, C

INTERNATIONAL SEARCH REPORT

Int. l. Application No

PCT/GB 98/02533

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 551 849 A (KASAI JUNICHI ET AL) 5 November 1985 see figures 1-3 see abstract	1-4, 6, 10, 12-15, 17, 21
A	see column 3, line 60 - column 4, line 64 ---	11, 23
X	PATENT ABSTRACTS OF JAPAN vol. 006, no. 194 (E-134), 2 October 1982 & JP 57 104396 A (NISSAN MOTOR CO LTD), 29 June 1982 see abstract	1, 2, 22
A	---	3-7, 9, 11-18, 20, 21, 23
A	US 4 751 419 A (TAKAHATA DAISUKE) 14 June 1988 see figures 1-3, 8-10 see abstract see column 4, line 27 - column 6, line 35 see column 8, line 61 - column 10, line 9 ---	1-23
A	US 4 720 867 A (IMAI HIROSHI ET AL) 19 January 1988 see figures 1-4 see abstract see column 2, line 63 - column 4, line 19 ---	1, 12
A	WO 97 09843 A (AZIMA HENRY ; HARRIS NEIL (GB); COLLOMS MARTIN (GB); VERITY GROUP P) 13 March 1997 see page 5, line 8 - page 13, line 3 see abstract see figures	1, 12
A	WO 97 09840 A (AZIMA HENRY ; HARRIS NEIL (GB); COLLOMS MARTIN (GB); VERITY GROUP P) 13 March 1997 see figures see abstract see page 5, line 5 - page 13, line 19 ---	1, 12
A	WO 97 16048 A (FIAT RICERCHE ; RUSPA GIACOMO (IT)) 1 May 1997 see figures 1, 5 see page 7, line 32 - page 8, line 26 ---	1, 12
A	US 3 422 921 A (WARNAKA GLENN E) 21 January 1969 see the whole document -----	1, 12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/02533

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4551849 A	05-11-1985	JP 1003434 B	20-01-1989
		JP 1521428 C	12-10-1989
		JP 58195396 A	14-11-1983
		JP 1003435 B	20-01-1989
		JP 1523509 C	12-10-1989
		JP 58210800 A	08-12-1983
		JP 1003436 B	20-01-1989
		JP 1523513 C	12-10-1989
		JP 59011100 A	20-01-1984
		JP 1003437 B	20-01-1989
		JP 1523514 C	12-10-1989
		JP 59012688 A	23-01-1984
US 4751419 A	14-06-1988	NONE	
US 4720867 A	19-01-1988	JP 1594284 C	14-12-1990
		JP 2018256 B	25-04-1990
		JP 60033147 A	20-02-1985
WO 9709843 A	13-03-1997	AU 6880196 A	27-03-1997
		AU 6880296 A	27-03-1997
		AU 6880396 A	27-03-1997
		AU 6880496 A	27-03-1997
		AU 6880596 A	27-03-1997
		AU 6880696 A	27-03-1997
		AU 6880796 A	27-03-1997
		AU 6880896 A	27-03-1997
		AU 6880996 A	27-03-1997
		AU 6881096 A	27-03-1997
		AU 6881296 A	27-03-1997
		AU 6881396 A	27-03-1997
		AU 6881496 A	27-03-1997
		AU 6881596 A	27-03-1997
		AU 6881696 A	27-03-1997
		AU 6881896 A	27-03-1997
		AU 6881996 A	27-03-1997
		AU 6882096 A	27-03-1997
		AU 6882196 A	27-03-1997
		AU 6882296 A	27-03-1997
		AU 6882396 A	27-03-1997
		CA 2230053 A	13-03-1997
		CA 2230064 A	13-03-1997
		CA 2230075 A	13-03-1997
		CA 2230104 A	13-03-1997
		CA 2230154 A	13-03-1997
		CA 2230155 A	13-03-1997
		CA 2230161 A	13-03-1997
		CA 2230234 A	13-03-1997
		CA 2230438 A	13-03-1997
		CA 2230444 A	13-03-1997
		CA 2230449 A	13-03-1997
		CA 2230461 A	13-03-1997
		CA 2230701 A	13-03-1997
		CA 2230702 A	13-03-1997
		CA 2230704 A	13-03-1997
		CN 1194085 A	23-09-1998
		CN 1194086 A	23-09-1998
		CZ 9800572 A	15-07-1998

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/02533

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9709843 A		CZ 9800573 A	15-07-1998
		CZ 9800574 A	15-07-1998
		CZ 9800575 A	15-07-1998
		CZ 9800576 A	11-11-1998
		CZ 9800577 A	15-07-1998
		CZ 9800578 A	15-07-1998
		CZ 9800579 A	15-07-1998
		CZ 9800580 A	15-07-1998
		CZ 9800581 A	15-07-1998
		CZ 9800582 A	15-07-1998
		CZ 9800583 A	15-07-1998
WO 9709840 A	13-03-1997	AU 6880196 A	27-03-1997
		AU 6880296 A	27-03-1997
		AU 6880396 A	27-03-1997
		AU 6880496 A	27-03-1997
		AU 6880596 A	27-03-1997
		AU 6880696 A	27-03-1997
		AU 6880796 A	27-03-1997
		AU 6880896 A	27-03-1997
		AU 6880996 A	27-03-1997
		AU 6881096 A	27-03-1997
		AU 6881296 A	27-03-1997
		AU 6881396 A	27-03-1997
		AU 6881496 A	27-03-1997
		AU 6881596 A	27-03-1997
		AU 6881696 A	27-03-1997
		AU 6881896 A	27-03-1997
		AU 6881996 A	27-03-1997
		AU 6882096 A	27-03-1997
		AU 6882196 A	27-03-1997
		AU 6882296 A	27-03-1997
		AU 6882396 A	27-03-1997
		CA 2230053 A	13-03-1997
		CA 2230064 A	13-03-1997
		CA 2230075 A	13-03-1997
		CA 2230104 A	13-03-1997
		CA 2230154 A	13-03-1997
		CA 2230155 A	13-03-1997
		CA 2230161 A	13-03-1997
		CA 2230234 A	13-03-1997
		CA 2230438 A	13-03-1997
		CA 2230444 A	13-03-1997
		CA 2230449 A	13-03-1997
		CA 2230461 A	13-03-1997
		CA 2230701 A	13-03-1997
		CA 2230702 A	13-03-1997
		CA 2230704 A	13-03-1997
		CN 1194085 A	23-09-1998
		CN 1194086 A	23-09-1998
		CZ 9800572 A	15-07-1998
		CZ 9800573 A	15-07-1998
		CZ 9800574 A	15-07-1998
		CZ 9800575 A	15-07-1998
		CZ 9800576 A	11-11-1998
		CZ 9800577 A	15-07-1998
		CZ 9800578 A	15-07-1998
		CZ 9800579 A	15-07-1998

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/02533

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9709840 A		CZ 9800580 A	15-07-1998
		CZ 9800581 A	15-07-1998
		CZ 9800582 A	15-07-1998
		CZ 9800583 A	15-07-1998
WO 9716048 A	01-05-1997	IT T0950857 A	21-04-1997
		IT T0960065 A	01-08-1997
		IT T0960296 A	17-10-1997
		EP 0856238 A	05-08-1998
US 3422921 A	21-01-1969	DE 1658909 A	27-04-1972
		GB 1185352 A	25-03-1970